

## P L U (A) -FL-TP#-M#-X-18-B -L0.5 -D0.25 18.25 36.25 /C

### Model series

Side Wall Panel **P**

### RA opening

Stamped Louvered **L**  
 Grille Louvered **A**  
 Perimeter **P**  
 Zero RA Opening (access only) **O**  
 Slotted **S**

### Door (Hinge)

Up Swing (removable) **U**  
 Down Swing (removable) **D**  
 Side Swing (non-removable) **S**  
 Side Swing (invertible) **I**  
 Side Swing (loose for removal) **L**  
 Non-Hinged (removable) **O**  
 Fixed in Place **F**  
 Rivet Hinges **H**

### Frame

#### Optional information

Profile Air Way 1.1" (default) **A**  
 Profile Air Way 1.6" **B**  
 Profile Air Way 2.1" **C**

### Frame options

Mud-in Flange (12%) **-MI**  
 Narrow Flange 0.75 (default is 1.25) (3%) **-N**  
 No Frame (-35%) **-NF**  
 Flangeless (12%) **-FL**  
 Narrow Mud-in (12%) **-FL2**  
 Removable Core (15%) **-R**  
 Increased Access (15%) **-IA**  
 Aluminum Frame (15%) **-AL**  
 Mounting Style (default 4 holes on sides) (\$6) **-MS#**  
 Mounting Style Gyproc (\$10) **-MG#**

### Securing options & quantity

Tamper-Proof Snakeeye Screw (OPT) **TP#**  
 Screws Slotted (OPT) **-SS#**  
 Hex Quarter Turn Latch (OPT) **-H#**  
 Slotted Quarter Turn Latch (OPT) **-S#**  
 Key-Lock (OPT) **-K#**  
 Concealed Latch (OPT) **-CL#**  
 Spring Latch (OPT) **-SL#**  
 Safety Chain (\$2) **-SC#**  
 Snap Down Arm (\$1) **-SA#**

(Where # is quantity)

### Closing options & quantity

Magnet Catch (Default) (OPT) **-M#**  
 Mechanical Catch (OPT) **-MC#**  
 Magnetic Touch Latch (OPT) **-ML#**  
 Touch Latch (OPT) **-TL#**

(Where # is quantity)

### Finishes

/C (See finish chart) Custom

### Opening height

36.25 36.00 Collar (example)

### Opening width

18.25 18.25 Collar (example)


### Panel depth

From door surface to unit.

Default (no need to specify, 2)

**-D 0.5** 0.5  
**-D 0.75** 0.75  
**-D 1** 1  
 ...  
**-D 3.75** 3.75  
**-D 4** 4

¼" increments upto 4"




### Lip height

Default (no need to specify, 0.25)


**-L 0.25** 0.25  
**-L 0.5** 0.5  
**-L 0.625** 0.625

1/8" increments"



### Other options

**-B** (6%) Removable Baffle  
**-C** (12%) Control Panels  
**-GK** (\$6) Flange Gasket  
**-GN** (\$6) Neck Gasket  
**-GR** (\$6) Rear Gasket  
**-GD** (\$6) Door-to-Frame Gasket  
**-AS** (55%) Fresh Air Intake Slots  
**-LT** (100%) Light (LED) Panel  
**-FT** (\$10) Filter Holder  
**-BK** (18%) Blocked Air  
**-GL** (\$6) Grille



### Material AWG

Default (no need to specify, frame 22, door 24 ga)

**-18** (37%) 18 Gauge Frame and Door  
**-20** (18%) 20 Gauge Frame and Door  
**-22** (6%) 22 Gauge Frame and Door  
**-24** (-35%) 24 Gauge Frame and Door

### Door options

**N/A** Insulated  
**-X** (5%) Non-insulated  
**-T#** (\$6) Thermostat Mountable ADA  
**-RH** (\$6) Reinforced Hinge  
**-2D** (5%) Two Doors  
**-3D** (5%) Three Doors  
**-ND** (-35%) No Door  
**-RS** Right Swing  
**-GH** (\$6) Gripping Handle

